

SANKHLA INDUSTRIES
ARAMID FABRIC SPECIFICATIONS

Sl No	Fiber	Weave	Denier	Ends/Inch warp	Ends/Inch fil	GSM	Width inches	Weight in GLM
1	Aramid	Plain	400	28	28	0.098	69	0.172
2	Aramid	plain	500	34	34	0.149	69	0.261
3	Aramid	Plain	500	28	28	0.122	69	0.215
4	Aramid	2:2	500	34	34	0.149	69	0.261
5	Aramid	Plain	600	28	28	0.147	69	0.258
6	Aramid	Plain	600	34	34	0.178	69	0.313
7	Aramid	2X	600	34	34	0.178	69	0.313
8	Aramid	Plain	750	24	24	0.157	69	0.276
9	Aramid	Plain	750	26	26	0.171	69	0.299
10	Aramid	Plain	800	18	18	0.126	64	0.205
11	Aramid	Plain	800	34	34	0.238	69	0.417
12	Aramid	Plain	840	19.5	19.5	0.143	69	0.251
13	Aramid	Plain	840	23	23	0.169	69	0.296
14	Aramid	Plain	840	26	26	0.191	63	0.306
15	Aramid	Plain	850	23	23	0.171	69	0.300
16	Aramid	Plain	850	24	24	0.178	69	0.313
17	Aramid	Plain	3000	17	17	0.446	63	0.714
18	Aramid	Plain	3000	11	11	0.289	63	0.462
19	Aramid	Plain	1000	31	31	0.271	63	0.434

Note : All grades are with WR (water repellent) treatment coated.